

CMV SHARPER FINISH, INC.

**SINGLE OPERATOR IRONERS
TECHNICAL DATA
MINI RITE / FINISH RITE /
IMPRESS 950**

T H E I R O N E R P E O P L E



All of the models covered in this brochure have separate Descriptive and Installation Dimension brochures giving detailed information. Contact CMV Sharper Finish for this information. In view of CMV's policy of providing the best products possible, we reserve the right to change specifications and appearance without notice. Contact the Sales Department for exact specifications, dimensions, and product approvals. CMV manufactures over 100 different ironer and folder models that are sold throughout the world.

© 2010 Form CMV2125

**CMV SHARPER FINISH,
INC.**

4500 Augusta Boulevard
Chicago, Illinois 60651
USA

Phone: 773-276-4800

Fax: 773-276-6878

E-mail: sales@cmvsharperfinish.com

www.ironerpeople.com

MINI RITE	Electrically Heated
Finishing Surface Width-Inches (mm)	36 (914)
Heated Roll Diameter-Inches (mm)	7 (148)
Electrical Requirements-H.P. (kW)	1/4 (.187)
Electrical Requirements-Heating kW	5.3
Net Weight-Pounds (kg)	535 (273)
Crated Weight-Pounds (kg)	600 (273)
Crated Size L x W x H Inches (mm)	62x25x57 (1581x635x1448)

FINISH RITE	Gas Heated Model	Electrically Heated Model
Finishing Surface Width-Inches (mm)	48, 60 (1219, 1524)	48, 60 (1219, 1524)
Heated Roll Diameter-Inches (mm)	7 (148)	7 (148)
Gas Inlet - Inches	1/2	-
Electrical Requirements-H.P. (kW)	1/4 + 1/50 (.187 + .15)	1/4 + 1/50 (.187 + .15)
Electrical Requirements-Heating kW		
48" (1219 mm) model	-	7
60" (1524 mm) model	-	8.8
Maximum Gas Input-B.T.U./hr. (Cal. kg/hr.)		
48" (1219 mm) model	24,000 (6048)	-
60" (1524 mm) model	30,000 (7560)	-
Net Weight-Pounds (kg)		
48" (1219 mm) model	490 (222)	510 (229)
60" (1524 mm) model	553 (249)	570 (256)
Crated Weight-Pounds (kg)		
48" (1219 mm) model	550 (247)	570 (256)
60" (1524 mm) model	600 (272)	620 (279)
Crated Size L x W x H Inches (mm)		
48" (1219 mm) model	75x29x58 (1905x724x1461)	75x29x58 (1905x724x1461)
60" (1524 mm) model	87x29x58 (2210x724x1461)	87x29x58 (2210x724x1461)
Canopy Blower Discharge Size Inches (mm) Round		
48" (1219 mm) model	4 (102)	4 (102)
60" (1524 mm) model	4 (102)	4 (102)

IMPRESS	Model G950	Model S950	Model E950
Finishing Surface Width-Inches (mm)	56, 66, 82 (1423, 1677, 2159)	56, 66, 82 (1423, 1677, 2159)	56, 66, 82 (1423, 1677, 2159)
Heated Roll Diameter-Inches (mm)	12 (305)	12 (305)	12 (305)
Gas Inlet - Inches	1/2	-	-
Steam Inlet - Inches	-	1/2	-
Condensate Return - Inches	-	1/2	-
Maximum Steam Pressure - P.S.I. (ATU)	-	150 (10)	-
Electrical Requirements-H.P. (kW)	1/3 + 1/50 (.249 + .15)	1/3 + 1/50 (.249 + .15)	1/3 + 1/50 + 1/50 (.249 + .15 + .15)
Electrical Requirements-Heating kW			
56" (1423 mm) model	-	-	14
66" (1677 mm) model	-	-	16
82" (2159 mm) model	-	-	22
Maximum Gas Input-B.T.U./hr. (Cal. kg/hr.)			
56" (1423 mm) model	70,000 (17,640)	-	-
66" (1677 mm) model	85,000 (21,420)	-	-
82" (2159 mm) model	95,000 (23,940)	-	-
Steam Consumption-Boiler H.P. (kg/hr.)			
56" (1423 mm) model	-	.56 (9)	-
66" (1677 mm) model	-	.66 (10)	-
82" (2159 mm) model	-	.85 (14)	-
Net Weight-Pounds (kg)			
56" (1423 mm) model	850 (382)	1000 (450)	900 (405)
66" (1677 mm) model	900 (405)	1050 (472)	950 (427)
82" (2159 mm) model	1160 (526)	1245 (565)	1165 (528)
Crated Weight-Pounds (kg)			
56" (1423 mm) model	990 (445)	1140 (513)	1040 (468)
66" (1677 mm) model	1050 (472)	1200 (540)	1100 (495)
82" (2159 mm) model	1504 (681)	1590 (721)	1510 (684)
Crated Size L x W x H Inches (mm)			
56" (1423 mm) model	89x37x62 (2261x940x1575)	89x37x62 (2261x940x1575)	89x37x62 (2261x940x1575)
66" (1677 mm) model	99x37x62 (2515x940x1575)	99x37x62 (2515x940x1575)	99x37x62 (2515x940x1575)
82" (2159 mm) model	124x37x63 (3150x940x1600)	124x37x63 (3150x940x1600)	124x37x63 (3150x940x1600)
Canopy Blower Discharge Size Inches (mm) Round			
56" (1423 mm) model	4 (102)	4 (102)	4 (102)
66" (1677 mm) model	4 (102)	4 (102)	4 (102)
82" (2159 mm) model	2 x 4 (102)	2 x 4 (102)	2 x 4 (102)